



## SUBJECT INDEX TO VOLUME 41

Acoustic emission, 152, 221  
Angle-ply laminates, 109

Carbon fibre (Poisson ratio), 1  
Carbon fibre surface, 21  
Carbon fibres (intrinsic properties), 287  
Carbon/carbon composites, 55  
Carbon/epoxy interface, 13  
Creep compliance, 310  
Cross-ply composites, 147  
Cut fibres (strain concentrations), 249

Damage accumulation, 221  
Damage zone model, 259  
Damping (in laminated composites), 379  
Delamination  
    promoters, 364  
    resistance, 82  
    resistors, 365  
Discontinuous fibre MMCs, 213  
Double rail shear test, 263  
Duplex fibre concept, 363

Failure analysis (woven composites), 129

Fibre  
    bridging, 55  
    coating, 354  
    pull-out, 350  
    structure, 19  
    surface treatments (sisal), 67

Finite elements, 129, 158, 194, 270, 381  
Fractographic analysis, 160  
Fracture (interleaved composites), 77  
Fracture toughness, 91  
    composites, 335

GRP tubes, 221

Hygrothermal ageing, 228

Impact damage tolerance, 89

Interface  
    carbon/epoxy, 13  
    control, 333  
    shear stresses, 241

Interfacial adhesion, 37  
Interfacial debonding, 350  
Interfacial studies, 31  
Interlaminar fracture, 147  
Interleaved composites, 77  
Intermittent coating, 354

Losipescu test, 263  
Liquid crystal domains, 179  
Loop test (carbon fibres), 289

Matrix rheology, 221  
MMCs, 213, 411  
Mode I fracture, 147  
Morphology (liquid crystal domains), 184

Notched composites, 257

Off-axis tests, 55  
Orthotropic plates, 47

PEEK composites, 303  
Poisson ratio (for carbon fibres), 1  
Pultruded GRP composites, 395

Shear failure analysis, 257  
Shrinkage stress control, 367  
Silane treatment (sisal/epoxy composites), 165

Sisal/epoxy composites, 165  
Sizes, 24  
Stiffness reduction (MMCs), 421  
Strain concentration factors, 237  
Stress analysis (non-classical), 63  
Stress concentration factor, 47  
Structure of carbon fibres, 19  
Superposed hydrostatic stress (effect on strength), 395  
Surface treatment, 21

Thermal buckling, 109  
Thermal residual stresses, 213  
Three-dimensional stress states (effect on damping), 379  
Toughness maps, 348  
Transverse properties, 15

Unidirectional composites, 237

Viscoelastic effects (PEEK composites), 303

Woven hybrid composites, 129



## AUTHOR INDEX TO VOLUME 41

Aboudi, J., 411  
Ansell, M. P., 165  
Ardic, S. E., 63  
Benzeggagh, M. L., 147  
Bisanda, E. T. N., 165  
Chang, J. S., 109  
Chen, S. F., 77  
Chikugo, R., 55  
D'Amore, A., 303  
Dutta, I., 193  
Ghorbel, I., 221  
Gibson, R. F., 379  
Grattier, J., 221  
Harding, J., 129  
Hecini, M., 147  
Hinrichsen, G., 179  
Hollmann, K., 257  
Hughes, J. D. H., 13  
Hwang, S. J., 379  
Jang, B. Z., 77  
Jing, G., 147  
Kim, J. K., 333  
Kimura, S., 55  
Krucinska, I., 1, 287  
Laksimi, A., 147  
Leu, S. Y., 109  
Li, Y. L., 129  
Mai, Y. W., 333  
Mansmann, U., 179  
Matsuo, Y., 55  
Meretz, S., 179  
Nicolais, L., 303  
Ochiai, S., 237  
Paley, M., 411  
Parry, T. V., 409  
Peters, P. W. M., 237  
Pompo, A., 303  
Roelandt, J. M., 147  
Ruiz, C., 129  
Santare, M. H., 63  
Schulte, K., 237  
Sigley, R. H., 395  
Stypka, T., 1  
Tanabe, Y., 55  
Taniguchi, K., 55  
Valentin, D., 221  
Wronski, A. S., 395  
Yao, W. X., 47  
Yasuda, E., 55  
Yrieix, M. C., 221  
Yu, X. L., 47